

Firestone Metal Products Company

Material Safety Data Sheet

March 12, 2009

Page: 1

SECTION 1: PRODUCT IDENTIFICATION

Product Name: Metal Roofing Products: UC-1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 14, 600, 601, 700; UR, HR, VR, 5VC, Flat Lock, ES-1, 2, 3, 4; sheet and coil stock, UNA-Edge DE, GS, CO; Brake metal

Chemical Name / Synonym: Revere Copper – Evergreen or Patina Copper, ASTM B370, B882

Chemical Family: None

24-Hour Emergency Phone: (800) 424-9300 CHEMTREC

Manufacturer's Name: Firestone Metal Products Company

Manufacturer's Address: 250 West 96th Street, Indianapolis, IN 46260

NFPA Hazard Rating: Health 1, Flammability 0, Reactivity 0

HMIS Hazard Rating: Health 1, Flammability 0, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
Copper	None	7440-50-8	≥99.5	1 mg/m ³ (dust) TLV 1 mg/m ³ (dust) PEL 0.2 mg/m ³ (fume) TLV 0.1 mg/m ³ (fume) PEL

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: Inhalation and skin.

Signs and Symptoms of Exposure: General handling of metal products typically do not present a health hazard. Sharp metal edges may cause skin cuts.

Upon welding, cutting, or welding on materials the following signs and symptoms of exposure:

Dusts and fumes generated during welding, cutting or welding activities can cause irritation to the eyes, respiratory tract and mucous membranes. A metallic or sweet taste sensation and/or discoloration of the skin and hair may occur in some instances to high exposures. Exposures to high concentrations of copper may cause gastrointestinal distress and conditions similar to metal fume fever; symptoms including muscular pain, chills, nausea and vomiting. Symptoms typically last for 24-48 hours, and are not life-threatening nor cause any permanent damage.

Medical Conditions Aggravated by Exposure: As a fume or dust, chronic respiratory disorders, including (but not limited to) asthma, chronic bronchitis and emphysema.

Chronic Effects: No chronic effects are expected due to general handling or heating of metal products.

Carcinogenicity: None.

Firestone Metal Products Company

Material Safety Data Sheet

March 12, 2009

Page: 2

SECTION 4: FIRST AID MEASURES

First Aid Procedures: Treat skin cuts via washing wound with soap and clean water, and apply antibiotic.

If particles from this material contact the eyes, hold eyelids open and flush immediately with a gentle stream of water for at least 15 minutes, preferably at an eyewash fountain. If particles become imbedded, or irritation continues, get medical attention. Following skin contact, clean immediately by washing affected area with soap and water. In case of inhalation of fumes or dusts, remove to fresh uncontaminated air. Administer oxygen if breathing is labored. Give artificial respiration if breathing has stopped. Get medical attention immediately if oxygen or artificial respiration are administered. While an unlikely means of exposure, in case of accidental ingestion, do not induce vomiting. Get medical attention and advise the physician of the nature of the material.

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media: Not applicable. Material will not burn unless involved in an intense fire supported by surrounding materials. In this case, extinguish using suitable media for surrounding materials.

Hazardous Combustion Products: Various metal oxides and carbon oxides.

Recommended Fire Fighting Procedures: No special procedures recommended for solid material. Do not permit water to come in contact with molten metal.

Unusual Fire and Explosion Hazards: None for solid material. Small chips, dust or other fines may be readily ignitable, generating considerable heat. Molten metal will splatter when it comes in contact with water.

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled: Not Applicable for solid material. When cleaning up fine dusts, avoid creating airborne dust. Use non-sparking tools, and avoid water.

Precautions to Be Taken in Handling and Storing: Keep dry.

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Activities involving the generation of high amounts of fine dusts and/or fumes should be evaluated to determine if additional local exhaust is necessary. If a local exhaust system is used, explosion-proof equipment may be warranted.

Respiratory Protection: Activities involving the generation of high amounts of fine dusts and/or fumes should be evaluated to determine if a NIOSH approved air purifying respirator may be appropriate based on employer-determined exposure levels. Air supplied or SCBA respirators may be required when the measured chemical concentration exceeds the capacity of the air purifying respirator or when personal exposure levels are unknown.

Firestone Metal Products Company

Material Safety Data Sheet

March 12, 2009

Page: 3

Eye Protection:	Safety glasses with side shields may be warranted when cutting or grinding on this product. Employer-determined protective eye ware for welding, torching or other hot-work activities is required.
Skin Protection:	Cut-resistant gloves may be warranted while handling solid material. Welding or other hot-work gloves may be warranted when carrying out welding, cutting or other hot-work activities involving this material.
Other:	Other protective clothing may be warranted depending upon the activities involving this material. The employer must make this determination.
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking or smoking and at the end of each shift.

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Solid metal, blue-green color, with no odor.		
Flash Point:	Not Applicable	Lower Explosive Limit:	Not Applicable
Method Used:	Not Applicable	Upper Explosive Limit:	Not Applicable
Evaporation Rate:	Not Applicable	Boiling Point:	Not Applicable
pH (undiluted product):	Not Applicable	Melting Point:	1976-1981 °F
Solubility in Water:	Negligible	Specific Gravity:	8.9
Vapor Density:	Not Applicable	Percent Volatile:	Not Applicable
Vapor Pressure:	Not Applicable		

SECTION 9: STABILITY AND REACTIVITY

Thermal Stability:	Stable
Hazardous Polymerization:	Will not occur
Conditions to Avoid:	None when material is in solid form. When dusts, chips or other fines are present, avoid water, strong oxidizers, acids, alkalis, and halogenated compounds.

SECTION 10: TRANSPORTATION

Regulatory Agency:	Not Regulated
Proper Shipping Name:	Not Applicable
Hazard Classification:	Not Applicable
Identification Number:	Not Applicable
Labels Required:	Not Applicable
Other Requirements:	Not Applicable

Firestone Metal Products Company
Material Safety Data Sheet

March 12, 2009

Page: 4

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments:	None.
Date of Previous MSDS:	January 11, 2008
Changes Since Previous MSDS:	Company name change
Telephone Number for Additional Information:	(317) 575-7190

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Metal Products Company, a subsidiary of Firestone Diversified Products, LLC, assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Metal Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.