



# UltraPly™ TPO Large Pipe Flashings

**Item Numbers:**     **W56TPO3013 (White)**  
                          **W56TPOT013 (Tan)**  
                          **W56TPOG013 (Gray)**

## DESCRIPTION:

Firestone UltraPly TPO Large Pipe Flashings are specifically designed for flashing of large round penetrations between 6" (150 mm) and 8" (200 mm). The pipe flashing fits various penetration sizes and it shall be cut at the correct place to ensure a tight fit before installation.

## METHOD OF APPLICATION:

1. Penetration shall be clean of prior flashings or foreign material.
2. Cut out a circle on the outside of a level ring of the pipe flashing that is smaller than the penetration.
3. Cut the extra material from the pipe flashing base around the indented circle.
4. Weld the flashing into place and install the clamp and sealant per current UltraPly TPO specifications.

## PRODUCT DATA:

**Material:** Thermoplastic Polyolefin (TPO)  
**Colors:** White, Tan, Gray  
**Size:** Fits round penetrations with outside diameters of 6" (150 mm) to 8" (200 mm)  
**Clamp:** All stainless steel - quick release - worm gear type

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



## PACKAGING:

UltraPly TPO Large Pipe Flashings are packaged with 10 units per carton along with 10 stainless steel clamps.

## PRECAUTIONARY DATA:

- Exercise caution when lifting, moving, transporting, storing or handling Firestone UltraPly TPO Pipe Flashing to avoid sources of puncture, physical damage or chemical contamination.
- Contact Firestone Roofing System Solutions Department for specific recommendations regarding chemical or waste product compatibility with Firestone UltraPly Pipe Flashing.
- Refer to Material Safety Data Sheets for all applicable components of UltraPly Systems.

## LEED INFORMATION:

Post Consumer Recycled Content: 0%  
Post Industrial Recycled Content: 0%  
Manufacturing Location: Wellford, SC

**Firestone Building Products Company, LLC**  
250 W. 96<sup>th</sup> Street, Indianapolis, IN 46260  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpc.com](http://www.firestonebpc.com)