

Firestone
BUILDING PRODUCTS**QuickSeam™**
Curb Flashing**Firestone Item Number: W56RAC1623****DESCRIPTION:**

QuickSeam Curb Flashing is 18" (457.2 mm) wide 60 gauge non-reinforced RubberGard™ membrane with 3" (76.2 mm) wide tape factory laminated along one edge. The 3" (76.2 mm) tape portion is used to splice the QuickSeam Curb Flashing to the roof membrane. The balance of the QuickSeam Curb Flashing is applied to the vertical surface with Firestone EPDM Bonding Adhesive BA-2004 or Water-Based Bonding Adhesive to hold the membrane in place and terminated using an approved termination detail.

METHOD OF APPLICATION:

1. Use Firestone QuickPrime™ Plus and QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane area to receive tape.
2. Refer to Firestone Specifications and Details.
3. Application temperature range is between -10 °F (-23 °C) and 120 °F (49 °C).
4. Refer to application instructions for specifics: Technical Database, www.firestonebpco.com

PHYSICAL PROPERTIES:**QUICKSEAM TAPE**

Base:	Rubber Polymers
Color:	Black
Solvents:	None
Solids:	100%
Cure State:	Cured
Thickness:	0.030" ± 0.005" (0.762 mm ± 0.127 mm)
Width:	3" (77 mm)

RUBBERGARD EPDM MEMBRANE

Base:	EPDM
Color:	Black
Solvents:	None
Cure State:	Cured
Thickness:	0.060" ± 0.005"
Width:	18" (457.2 mm)
Type:	Non-reinforced

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.

**PACKAGING:**

- 50' rolls, 1 roll per carton
- 24 Cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

SHELF LIFE:

- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

STORAGE:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

PRECAUTIONARY INFORMATION:

Refer to Material Safety Data Sheet (MSDS).

LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Locations:	Prescott, AR

PATENTS:

The products contained herein, or the methods of their use, may be covered by one or more of the following United States Patents: 5,242,727; 5,520,761; 5,976,292; 6,426,129.

Firestone Building Products Company
250 W. 96th Street, Indianapolis, IN 46260
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com