



Concrete Drive Fastener

Firestone Item Number:

1-1/2"	W56RAC4320	5"	W56RAC4327
2"	W56RAC4321	5-1/2"	W56RAC4328
2-1/2"	W56RAC4322	6"	W56RAC4349
3"	W56RAC4323	6-1/2"	W56RAC4350
3-1/2"	W56RAC4324	7"	W56RAC4351
4"	W56RAC4325	7-1/2"	W56RAC4352
4-1/2"	W56RAC4326	8"	W56RAC4353

DESCRIPTION:

Firestone Concrete Drive fasteners are used in roofing applications in conjunction with Firestone Insulation Plates for the attachment of roofing insulation, and base sheets, or attachment of Firestone Metal Batten Strips, Seam Plates, Termination Bars, and other accessories into structural concrete substrates.

Note: Do not use with Polymer Batten Strips.

METHOD OF APPLICATION:

- Use a rotary hammer or hammer drill in hammer mode to pre-drill a pilot hole with a 1/4" (6.3 mm) ANSI 0.260" to 0.268" diameter (6.6 - 7.3 mm) drill bit. Pilot hole must be drilled 1/2" (12.7 mm) deeper than the required embedment.
- Install the Concrete Drive using a 3 lb (6.6 kg) hammer until the fastener head is seated firmly against the plate. Do not overdrive the fastener causing substrate damage.

Note: Minimum required embedment is 1-1/4" (31.7 mm) into the concrete substrate.

PRECAUTIONARY DATA:

- Eye protection must be worn during the installation of concrete drives.
- Do not use over structural concrete substrates which are less than 3" (76 mm) thick at the point of attachment.

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
Material:	AISI C-1038-1040, heat
Core Hardness:	Rc 37-43
Corrosion Coating:	Black epoxy coating
Diameter:	1/4" (6.3 mm) Nominal

<u>Drive Length</u>	<u>Pieces/ Carton</u>	<u>Cartons/ Pallet</u>
1-1/2" (38 mm) to 5-1/2" (140 mm) in 1/2" (13 mm) increments	500	40
6" (152 mm) to 8" (203 mm) in 1/2" increments	250	40

Determine required drive length as follows:

Select drive length to penetrate into structural concrete deck a minimum of 1-1/4" (32 mm).

LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	25%
Manufacturing Location:	New Rochelle, NY



Firestone Building Products Company
250 W. 96th Street, Indianapolis, IN 46260
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com