



## UltraPly™ TPO Coated Metal

**Item Numbers:**      **W56TPO3023 (White)**  
                                  **W56TPOG023 (Gray)**  
                                  **W56TPOT023 (Tan)**

**DESCRIPTION:**

Firestone UltraPly TPO Coated Metal is made from a flexible non-reinforced thermoplastic polyolefin membrane factory laminated to hot-dipped galvanized steel. Firestone UltraPly TPO Coated Metal can function as a flashing component for the Firestone UltraPly TPO System.

**METHOD OF APPLICATIONS:**

1. Install UltraPly TPO coated Metal with 1/8" to 1/4" (3 to 6 mm) between adjoining sections.
2. Install 2" (50 mm) wide duct tape over joints in UltraPly TPO Coated Metal.
3. Heat weld a 6" (150 mm) wide piece of UltraPly TPO Unsupported Flashing over the joint.
4. All welds to UltraPly TPO Coated Metal must be at least 1 1/2" (40 mm) wide.

**PHYSICAL PROPERTIES:**

	<b>TPO Coating</b>
Color:	White, Gray, or Tan
Thickness:	0.030" (0.76 mm)
	<b>Sheet Metal</b>
Type:	24 gauge G-90 hot dipped galvanized steel
Thickness:	0.023" (0.58 mm)
Length:	10' (120 ± 3/4"; 305 ± 20 mm)
Width:	4' (48 ± 1/2"; 152 ± 10 mm)

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



**STORAGE:**

Store material in original unopened packaging in a dry area away from sources of physical damage or chemical contamination.

**PACKAGING:**

- 10 sheets per pallet
- Weight per pallet: 670 lb (300 kg)

**LEED INFORMATION:**

Post Consumer Recycled Content:    22%  
 Post Industrial Recycled Content:    6%  
 Manufacturing Location:                Taylor, PA

**Firestone Building Products Company**  
 250 W. 96<sup>th</sup> Street, Indianapolis, IN 46260  
 Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpc.com](http://www.firestonebpc.com)