



Ceramic Coated Roofing Granules

Firestone Item Number:

W70RACGGWH (White)
W70RACGGBK (Black)

DESCRIPTION:

Ceramic coated roofing granules are made available in 50 lb (22.7 kg) metal pails.

METHOD OF APPLICATION:

Firestone recommends that granules be applied to areas of asphalt "bleed-out" while the asphalt is still in a molten state. Areas of "bleed-out" at inside and outside corners require application of granules.

PACKAGING:

Pail – 5 gallon (18.9 L)
Weight – 50 lb (22.7 kg)

SHIPPING INFORMATION:

Pallet Size: 48" x 39" (1.2 m x 1.0 m)
Pails Per Pallet: 36
Weight Per Pallet: 2,000 lb (907 kg)
Pallets Per Truckload: 24

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



PRODUCT DATA

PRECAUTIONS:

- Minimize the amount of dust generated when applying or handling this product. Use in well ventilated area.
- Review the Material Safety Data Sheet for more information.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Beech Grove, IN

Firestone Building Products Company
250 W. 96th Street, Indianapolis, IN 46260
Sales: (800) 428-4442 • Technical (800) 428-4511
www.firestonebpco.com