

# Firestone Building Products Company

## Material Safety Data Sheet

February 9, 2009

Page: 1

---

### SECTION 1: PRODUCT IDENTIFICATION

---

Product Name: I.S.O. Stick Part 2  
Chemical Name / Synonym: Polyurethane System Resin Component  
Chemical Family: None  
24-Hour Emergency Phone: (800) 424-9300 CHEMTREC  
Manufacturer's Name: Firestone Building Products Company  
Manufacturer's Address: 250 West 96<sup>th</sup> Street, Indianapolis, IN 46260  
NFPA Hazard Rating: Health 1, Flammability 1, Reactivity 0  
HMIS Hazard Rating: Health 1, Flammability 1, Reactivity 0

---

### SECTION 2: CHEMICAL COMPOSITION

---

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
Dipropylene Glycol	None	25265-71-8	<12	None Established
Decyl Alcohol, Ethoxylated	Ethoxylated Alcohol	26183-52-8	<10	None Established
Diethylene Glycol	None	111-46-6	<7	None Established
Non-Hazardous	None	TSCA Listed	>71	None Established

---

### SECTION 3: HAZARD IDENTIFICATION

---

Primary Route of Exposure: Inhalation, skin and eye contact.  
Signs and Symptoms of Exposure: May cause irritation to the eyes upon contact. May cause irritation to respiratory tract. While unlikely to be swallowed, ingesting the ingredient diethylene glycol can cause liver and kidney damage, CNS depression and nausea, with advanced stages of exposure including unconsciousness, coma and death.  
Medical Conditions Aggravated by Exposure: Pre-existing skin disorders, eye problems, or impaired liver or kidney function may be more susceptible to the effects of diethylene glycol and dipropylene glycol.  
Chronic Effects: Prolonged and/or repeated inhalation may cause damage to kidneys, liver and/or central nervous system. Adverse reproductive effects have been reported in animals following long term exposure to diethylene glycol.  
Carcinogenicity: None.

---

### SECTION 4: FIRST AID MEASURES

---

First Aid Procedures: For eyes, hold eyelids open and wash with gentle stream of water for at least 15 minutes preferably at eyewash fountain. For skin contact, wash affected area thoroughly with soap and water when time permits. For inhalation, remove to fresh uncontaminated air. If breathing is difficult, give oxygen and seek medical attention. While ingestion is not likely, if swallowed, do not induce vomiting; rather seek medical attention.

# Firestone Building Products Company

## Material Safety Data Sheet

February 9, 2009

Page: 2

---

### SECTION 5: FIRE FIGHTING PROCEDURES

---

Suitable Extinguishing Media:	Water spray, carbon dioxide, foam, or dry chemical.
Hazardous Combustion Products:	Carbon oxides.
Recommended Fire Fighting Procedures:	Wear impermeable protective clothing and self-contained breathing apparatus.
Unusual Fire and Explosion Hazards:	None known.

---

### SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

---

Steps to Be Taken in Case Material is Released or Spilled:	Isolate spill or leak area, absorb with inert material such as sawdust and place into container for proper disposal. Surfaces may be slippery.
Precautions to Be Taken in Handling and Storing:	Store in a dry, well-ventilated area at temperatures between 60° and 80° F. Spilled material may cause slippery surfaces. Keep container closed when not in use. Shelf life in original container is 8 months. Keep out of reach of children.

---

### SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Ventilation:	Use in a well ventilated location.
Respiratory Protection:	While not typically necessary, a NIOSH approved respirator may be needed if the user's exposure level exceeds levels that lead to health effects.
Eye Protection:	Safety glasses with side shields or goggles may be necessary to prevent eye contact.
Skin Protection:	Rubber, plastic or neoprene gloves may be necessary when handling this product.
Other:	None typically required under normal conditions.
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking or smoking and at the end of each shift. Wash contaminated clothing prior to reuse.

---

### SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance and Odor:	Red liquid with slight sweet odor.		
Flash Point:	375° F	Lower Explosive Limit:	Unknown
Method Used:	P-M	Upper Explosive Limit:	Unknown
Evaporation Rate:	Unknown	Boiling Point:	Unknown
pH (undiluted product):	Unknown	Melting Point:	Not Applicable
Solubility in Water:	Slight	Specific Gravity:	Unknown
Vapor Density:	Unknown	Percent Volatile:	Unknown
Vapor Pressure:	Unknown		

---

### SECTION 9: STABILITY AND REACTIVITY

---

Thermal Stability:	Stable. Do not heat.
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	Oxidizers, acids and alkalis.

**Firestone Building Products Company**  
**Material Safety Data Sheet**

February 9, 2009

Page: 3

---

SECTION 10: TRANSPORTATION

---

Regulatory Agency:	Not regulated
Proper Shipping Name:	Not applicable
Hazard Classification:	Not applicable
Identification Number:	Not applicable
Labels Required:	Not applicable
Other Requirements:	Not applicable

---

SECTION 11: MISCELLANEOUS INFORMATION

---

Additional Comments:	None.
Date of Previous MSDS:	September 29, 2008
Changes Since Previous MSDS:	Company name change
Telephone Number for Additional Information:	(317) 575-7190

DISCLAIMER

---

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, a subsidiary of Firestone Diversified Products, LLC, assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.