



## QuickSeam™ Pipe Flashing

**Firestone Item Number: W563581063**

**DESCRIPTION:**

QuickSeam Pipe Flashings are specifically designed to be used in roofing applications for flashing of round penetrations. QuickSeam Pipe Flashings will fit various penetrations and must be cut to correct pipe diameter before installation.

QuickSeam Pipe Flashings may be used to flash penetrations for both RubberGard™ EPDM as well as APP and SBS Modified Bitumen systems.

**METHOD OF APPLICATION:**

1. Clean the Rubbergard membrane using QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agents, dirt and other contaminants that will affect the finished bond.
2. Allow to dry according to the touch-push test.
3. Cut along the top edge of the ring on the QuickSeam Pipe Flashing corresponding to the size of the pipe.
4. Remove the release paper.
5. Install the pipe flashing and roll the flange with a silicone hand roller.
6. Install the clamping ring and Lap Sealant per Firestone Specifications and Details.
7. Install per specific requirements as outlined on the QuickSeam Pipe Flashing Technical Information Sheet located in the Firestone Asphalt Technical Manual.

**PHYSICAL PROPERTIES:  
MOLDED PIPE FLASHING**

<u>Property</u>	<u>Minimum Performance</u>
Material:	Molded EPDM
Color:	Black
Sizes:	Universal – Fits 1" O.D. to 6.875" O.D. (25.4 mm to 174.6 mm)
Clamp:	Stainless Steel - worm gear type (clamps are included)
Pipe Flange:	13" (33 cm) outside diameter
Thickness:	0.055" - 0.075" (1.4 mm - 1.9 mm)

This sheet is meant to highlight Firestone's products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.



**QUICKSEAM TAPE**

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymer
Color:	Black
Solvents:	None
Percent Solids:	100%
Cured State:	Cured
Thickness:	0.030" (0.762 mm) + 0.005" (0.13 mm)

Fits the Pipe Outside Diameters listed below:

1.000" - 1.375"	25.4 mm - 34.9 mm
1.625" - 1.875"	41.3 mm - 47.6 mm
2.000" - 2.625"	50.8 mm - 66.7 mm
2.750" - 3.625"	69.8 mm - 92.1 mm
4.000" - 4.500"	102.0 mm - 114.0 mm
5.000" - 5.563"	127.0 mm - 141.0 mm
6.000" - 6.875"	152.4 mm - 174.6 mm

*NOTE: For penetrations less than 1" in diameter, use Firestone QuickSeam Conduit Flashing.*

**PRECAUTIONARY DATA:**

- Refer to the Material Safety Data Sheet (MSDS).
- Do not install over uneven substrates.

**LEED INFORMATION:**

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Location:	Bensenville, IL

**PATENTS:**

The products contained herein, or the methods of their use, may be covered by one or more of the following United States Patents: 5,084,119; 5,204,148; 5,242,727; 5,520,761; 5,976,292; 5,985,981.

**Firestone Building Products Company**  
250 W. 96<sup>th</sup> Street, Indianapolis, IN 46260  
Sales: (800) 428-4442 • Technical (800) 428-4511  
[www.firestonebpc.com](http://www.firestonebpc.com)